

كتالوج طواحين مقاس

قدم 5.5 و 7 قدم

型号规格 Type		YS550-STD (5½ FT)				YS700-STD (7FT)			
		F	M	C	EC	F	M	C	EC
锥大端直径(mm) cone big end dia		1676(5½ ')				2134(7 ')			
给矿口尺寸(mm) Feed dim		209	241	269	368	278	334	369	460
排矿口调整范围(mm) Discharge Opening		16-38	22-51	25-64	38-64	19-38	25-51	31-64	38-64
产量(t/h) Capacity		180-340	256-414	297-630	428-675	378-720	603-990	783-1260	873-1351
主电机 Main motor	功率(kw) Power	220				315			
	转速(l/min) speed	490/985				490/985			
	电压(V) Voltage	6000				6000			
机器外形尺寸 Outling of machine	长(mm) Length	3911				4613			
	宽(mm) Weight	2870				3251			
	高(mm) Height	3771				4732			
机器重量(kg) Weight of machine		48780		47820					
备注 Remark		(1)机器的外形尺寸和重量不包括电机； (2) 产量系根据堆比重为1.6t/m3的标准物料。							

型号规格 Type		YS550-D (5½ FT)				YS700-D (7FT)			
		F	M	C	EC	F	M	C	EC
锥大端直径(mm) cone big end dia.		1676(5½ ')				2134(7')			
给矿口尺寸(mm) Feed diameter		70	89	133	133	105	133	178	203
排矿口调整范围(mm) Discharge Opening		5-13	6-13	10-19	13-19	5-16	10-19	13-25	16-25
产量(t/h) Capacity		90-209	136-281	190-336	253-336	190-408	354-508	454-599	508-653
主电机 Main motor	功率(kw) Power	220				315			
	转速(l/min) speed	490/985				490/985			
	电压(V) Voltage	6000				6000			
机器外形尺寸 Outling of machine	长(mm) Length	3971				4130			
	宽(mm) Weight	2870				3251			
	高(mm) Height	3771				4454			





